HIGHLIFE® COLLECTION



FreshWater® Salt System Ready



100% Filtration
SilentFlo Circulation



Moto-Massage® DX



Super Energy Efficient



Wireless Remote



Polymer Substructure & Base Pan

JETSETTER® LX



PeopleSeatingJetsVoltage3 SeatsLounge30 Jets230 V

Size

7' x 5'8" x 33" | 213 cm x 173 cm x 84 cm

Water Care

FreshWater® Salt System Ready



HIGHLIFE® COLLECTION

ETSETTER LX





SHELL COLORS



Alpine

White

lava











Pebble

Platinum Ivory Tuscan Sun

CABINET COLORS





Charcoal

Ice

Gray



Blackwood




Linen

Black



Brushed Nickel

COVER COLORS



CABINET AND SHELL COLOR OPTIONS*

Cabinet Colors	Java	Charcoal	Blackwood	Linen	Brushed Nickel
Shell Colors	Alpine White				
	Ice Gray	Ice Gray	Ice Gray	Ivory	Ice Gray
	Ivory	Platinum	Platinum	Tuscan Sun	Platinum
	Tuscan Sun	Tuscan Sun		Pebble	
	Pebble	Pebble			

LEGENDARY MASSAGE

30 Personalized-Control Jets

- Moto-Massage® Lounge
- · Soothing Stream® Seat
- · Precision® Jet Seat

EASY WATER CARE

Water Care System FreshWater® Salt System Ready **Filtration System** 100% No-bypass Filtration Exclusive, High-flow Tri-X® Filters

Unique, Dual-Action Filtration

LEADING ENERGY EFFICIENCY

Jet Pump Wavemaster® 9000; One-speed, 2.5 HP Continuous Duty,

5.2 HP Breakdown Torque

Circulation Pump SilentFlo 5000® for quiet, continuous filtration

Titanium No-Fault® 6,000 W / 230 V Heater

Multiple Layers of Foam Insulation; Certified to California Insulation

Energy Commission (CEC) and APSP 14 energy efficiency

standards for portable spas

Cover 3.5" to 2.5" tapered, 1.5 lb. density foam core, with hinge seal

SIZE

Dimensions 7' x 5'8" x 33" / 213 cm x 173 cm x 84 cm

CAPACITY

Seating Capacity 3 seats with lounge **Water Capacity** 250 gallons / 950 liters

515 lbs. / 235 kg dry; 3,125 lbs. / 1,425 kg filled** Weight

ADDITIONAL FEATURES

Cover Lifters CoverCradle®, CoverCradle II, Lift 'n Glide®,

or UpRite® (F/B only)

Steps Steps are available to match cabinet colors Bluetooth® Wireless Sound System (Optional) Entertainment IQ 2020® with wireless remote control **Control System**

230 V / 50 amp, 60 Hz

(Includes G.F.C.I. protected sub-panel) Luminescence® multi-color four-zone **Lighting System**